


AM6032 – Switch

DC – 26.5 GHz SP4T



Description


AM6032 is a reflective Single-Pole Four-Throw (SP4T) switch covering the DC to 26.5 GHz frequency range suited for a wide range of wireless applications. The AM6032 provides low insertion loss, flat frequency response, high isolation and linearity, and fast switching speed making this switch ideal for high frequency, low power transmit/receive applications. The AM6032 requires only a single positive supply and two positive control voltages. With internal 50 Ω matching, internal decoder circuitry, and low current draw all packaged in a 4mm QFN, the AM6032 represents a compact total PCB footprint with minimal size, weight, and power (low SWaP).



Features

- 2.0 dB Insertion Loss
- +40 dBm Input IP3
- >35 dB Isolation
- +3.3V to +5.0V Supply
- +3.3V to +5.0V Control
- 4mm QFN
- -40C to +85C Operation

Functional Diagram



Characteristic Performance






Table of Contents

Description	1	DC Electrical Characteristics	5
Features	1	RF Performance	5
Functional Diagram	1	Timing Characteristics	5
Characteristic Performance	1	State Table	5
Revision History	2	Typical Performance	6
Pin Layout and Definitions	3	Typical Application	8
Specifications	4	Evaluation PC Board	9
Absolute Maximum Ratings	4	Related Parts	9
Handling Information	4	Component Compliance Information	10
Recommended Operating Conditions	4		

Revision History

Date	Revision Number	Notes
June 17, 2020	1	Initial Revision

Pin Layout and Definitions



Pin Number	Pin Name	Pin Function
1	GND	Ground – Common
2	RF1	RF1 Output – 50 Ohms – DC Coupled. External DC Blocking Capacitor Required*
3, 4	GND	Ground – Common
5	RF2	RF2 Output – 50 Ohms – DC Coupled. External DC Blocking Capacitor Required*
6, 7	GND	Ground – Common
8	VDD	DC Power Input
9	GND	Ground – Common
10	B	Switch Control B
11	A	Switch Control A
12, 13	GND	Ground – Common
14	RF3	RF3 Output – 50 Ohms – DC Coupled. External DC Blocking Capacitor Required*
15, 16	GND	Ground – Common
17	RF4	RF4 Output – 50 Ohms – DC Coupled. External DC Blocking Capacitor Required*
18-21	GND	Ground – Common
22	RFC	RFC Input – 50 Ohms – DC Coupled. External DC Blocking Capacitor Required*
23, 24	GND	Ground – Common

***Note:** DC blocking caps not required if in series with other Atlanta Micro parts of the same reference voltage.

AM6032 – Switch

DC – 26.5 GHz SP4T



Specifications

Absolute Maximum Ratings

	Minimum	Maximum
Supply Voltage	-0.3 V	+6.0 V
RF Input Power		+27 dBm
Operating Junction Temperature	-40 C	+150 C
Storage Temperature Range	-55 C	+150 C

Note: Any device operation beyond the Absolute Maximum Ratings may result in permanent damage to the device. The values listed in this table are extremes and do not imply functional operation of the device at these or any other conditions beyond what is listed under Recommended Operating Conditions. Any part subjected to conditions outside of what is recommended for an extended amount of time may suffer from reliability concerns.

Handling Information

	Minimum	Maximum
Storage Temperature Range (Recommended)	-50 C	+125 C
Moisture Sensitivity Level	MSL 3	



Atlanta Micro products are electrostatic sensitive.
Follow safe handling practices to avoid damage

Recommended Operating Conditions

	Minimum	Typical	Maximum
Supply Voltage	+3.3 V	+5.0 V	+5.2 V
Operating Case Temperature	-40 C		+85 C
Operating Junction Temperature	-40 C		+125 C

AM6032 – Switch

DC – 26.5 GHz SP4T

DC Electrical Characteristics

(T = 25 °C unless otherwise specified)

Parameter	Testing Conditions	Minimum	Typical	Maximum
DC Supply Voltage		+3.3 V	+5.0 V	
DC Supply Current	VDD = +5.0 V		5 mA	
Power Dissipated	VDD = +5.0 V		25 mW	
Logic Level Low		0.0 V		+0.5 V
Logic Level High		+2.0 V		+VDD

RF Performance

(T = 25 °C unless otherwise specified)

Parameter	Testing Conditions	Minimum	Typical	Maximum
Frequency Range		DC		26.5 GHz
Insertion Loss	f = 0.1 GHz, RF1/RF4		-0.90 dB	
	f = 0.1 GHz, RF2/RF3		-0.85 dB	
	f = 10 GHz, RF1/RF4		-1.35 dB	
	f = 10 GHz, RF2/RF3		-1.30 dB	
	f = 26.5 GHz, RF1/RF4		-3.85 dB	
	f = 26.5 GHz, RF2/RF3		-3.60 dB	
Return Loss	RF1/RF4		-15 dB	
	RF2/RF3		-15 dB	
Output IP3	VDD = +5.0 V		+40 dBm	

Timing Characteristics

Parameter	Minimum	Typical	Maximum
Switching Speed (Path Enabled to Disabled)		10 ns	
Switching Speed (Path Disabled to Enabled)		10 ns	

Note: Switching speed measured without any control line filtering.

State Table

A	B	State
L	L	RFC → RF1
L	H	RFC → RF2
H	L	RFC → RF3
H	H	RFC → RF4


AM6032 – Switch

DC – 26.5 GHz SP4T


Typical Performance

(VDD = +5.0V, T = 25 °C unless otherwise specified)


Insertion Loss at +25C




Insertion Loss vs Temperature




RF1/RF4 Return Loss at +25C




RF2/RF3 Return Loss at +25C



Isolation at +25C



Isolation at +25C



AM6032 – Switch


DC – 26.5 GHz SP4T




Typical Performance (continued)

(VDD = +5.0V, T = 25 °C unless otherwise specified)


Input IP3 vs VDD - RF2/RF3




Input IP3 vs VDD - RF1/RF4




Input IP3 vs VDD - RF2/RF3



Input IP3 vs VDD - RF1/RF4



Typical Application



Recommended Component List (or equivalent):

Part	Value	Part Number	Manufacturer
C1-C5	0.1 μ F	04020BB104KW160	Passives Plus
C6	0.1 μ F	C1005X7R1H104K050BB	TDK
FB1	-	MMZ1005A222E	TDK


Notes:

- DC blocking capacitors should be high performance, low-loss, broadband capacitors for optimum performance
- RC filtering on the control lines is recommended to prevent digital noise from coupling to the RF path.
 - Select control line RC filter values based on desired logic source decoupling and switching speed.

AM6032 – Switch

DC – 26.5 GHz SP4T

Evaluation PC Board



***Note:** DC blocking capacitors not included on the AM6Q Evaluation Board. External DC blocks are required.

Related Parts

Part Number		Description		
AM6013	DC	to 20 GHz	SP4T, Reflective	
AM6016	DC	to 26.5 GHz	SPDT, Reflective	
AM6017	DC	to 26.5 GHz	SP4T, Reflective	
AM6029	DC	to 18 GHz	SP4T, Reflective	

Component Compliance Information

RoHS: Atlanta Micro, Inc. hereby certifies that all products comply with the EC Directive 2011/65/EC on the Restriction of Hazardous Substances, commonly known as EU-RoHS 6 and 10. All products supplied by Atlanta Micro shall be compliant with the European Directive 2011/65/EC based on the following substance list.

Substance List	Allowable Maximum Concentration
Lead (Pb)	<1000 PPM (0.1% by weight)
Mercury (Hg)	<1000 PPM (0.1% by weight)
Cadmium (Cd)	<75 PPM (0.0075% by weight)
Hexavalent Chromium (CrVI)	<1000 PPM (0.1% by weight)
Polybrominated Biphenyls (PBB)	<1000 PPM (0.1% by weight)
Polybrominated Diphenyl ethers (PBDE)	<1000 PPM (0.1% by weight)
Decabromodiphenyl Deca BDE	<1000 PPM (0.1% by weight)
Bis (2-ethylhexyl) Phthalate (DEHP)	<1000 PPM (0.1% by weight)
Butyl Benzyl Phthalate (BBP)	<1000 PPM (0.1% by weight)
Dibutyl Phthalate (DBP)	<1000 PPM (0.1% by weight)
Diisobutyl Phthalate (DIBP)	<1000 PPM (0.1% by weight)

REACH: Atlanta Micro, Inc. neither uses nor intentionally adds any of the substances considered to be a Substance of Very High Concern (SVHC) as defined by the EU Regulation (EC) No. 1907-2006 on Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH).

Conflict Materials: Atlanta Micro does not knowingly use materials that are sourced from the Democratic Republic of Congo (DRC) or any other known conflict regions. Atlanta Micro's supply chain is comprised of sources that are both environmentally and socially responsible. We periodically review this requirement with our vendors to ensure continued compliance.

Atlanta Micro takes its responsibility as a global partner seriously and will use due diligence within our supply chain to ensure all standards are met to the best of our knowledge.