

PE15

UL/GS Listed Gigabit PoE Injector



Description

The PE15 is a single port gigabit POE Mid-spans offer a compact and cost effective, fully IEEE 802.3af compliant solution for remote powering of wireless LAN (WAN) access points, IP Security cameras, VoIP telephone and other low port density installations.

The PE15 PoE Mid-spans eliminate the need for external power supply and its associated AC/DC power cabling, providing a compact, affordable, safe and reliable power solution over existing Ethernet infrastructure.

Features

- IEEE802.3, IEEE 802.3u, IEEE802.3ab, IEEE802.3af.
- Up to 15.4W of Power on 2-pairs.
- Supports 10/100/1000 Base-T applications
- LED indicators power input and PoE output indication
- Distance up to 100 meters
- Internal AC/DC converter - no need for external power brick
- Easy plug-and-play installation

Specifications

Description	
Interfaces	1 x RJ-45 Connector for Data 1 x RJ-45 Connector for PoE out +Data
Indicators	Power, PoE
Standard	IEEE802.3af
Power Method	100-240VAC, 50/60Hz

Output Voltage	52VDC
PoE Budget	15.4W
Output PoE Pin Assignment	V+ (RJ45 Pin7,8), V- (RJ45 Pin 1,2)
Dimensions	145.5 x 61.5 x 40 mm
Weight	0.45KG
Operating Temperature	0 to 40°C
Storage Temperature	-10 to 70°C
Operating Humidity	5 to 95% Noncondensing
Electromagnetic Emission & Immunity	FCC (Part15, Class B) CE (EN55022/24) C-Tick (AS/NZS55022/24) CCC (GB4943) KCC (K60950-1) BSMI (CNS13438)
Safety Approvals	UL/cUL (EN6095-1) ICES (ICES-003) GS (EN60950-1) CE/LVD (EN60950-1) SAA (AS/NZS60950-1) CCC (GB4943) KC (K60950-1) PSE (J60950-1) NOM (IEC60950-1) S-mark (IEC60950-1) BSMI (CNS14336) EAC (LEC60950-1) BIS (BISIS13252)
Package List	
PoE Injector	1pcs
User Manual	1pcs

Order Information

Models	
PE15	Gigabit PoE Injector (15.4W)